

|                |   |
|----------------|---|
| Product name   | <b>Asalite LED Floodlight Slim 20W 6500K (1800 lumens) + Sensor</b> |
| Product code   | <b>ASAL0140</b>   |
| EAN-code       | <b>5999565662776</b>  |
| Packaging unit | <b>1pcs, 40pcs/carton</b>   |



## Technical Details

|  |                          |
|--|--------------------------|
| Power                                  | <b>20 W</b>              |
| Socket                                 | <b>AC</b>                |
| Luminosity                             | <b>1 800 lumen</b>       |
| Colour temperature                     | <b>6 500 K</b>           |
| Dimmable                               | <b>no</b>                |
| IP protection                          | <b>IP 65</b>             |
| Dimension                              | <b>118 x 165 x 45 mm</b> |
| Power grid                             | <b>AC 220-240 V</b>      |
| Frequency                              | <b>50/60 Hz</b>          |
| Lifetime                               | <b>25 000 hours</b>      |
| On/Off Cycles                          | <b>12 500</b>            |
| Shade colour                           | <b>transparent</b>       |
| Technology                             | <b>SMD LED</b>           |
| Product form                           | <b>floodlight</b>        |
| Product material                       | <b>glass/aluminium</b>   |
| Product colour                         | <b>black</b>             |
| Supply cable length                    | <b>35 cm</b>             |
| Beam angle                             | <b>120 °</b>             |
| Luminous efficacy                      | <b>90 lumen/watt</b>     |
| Colour rendering factor (Ra)           | <b>&gt;80</b>            |
| Power factor (Pf)                      | <b>&gt;0,9</b>           |
| Equivalence to conventional lamp power | <b>104 W</b>             |
| Beam angle of the sensor               | <b>&gt; 180 °</b>        |
| Range of motion sensor                 | <b>12 m</b>              |
| Operating temperature                  | <b>-15 °C- +50 °C</b>    |
| Product weight                         | <b>315 g</b>             |
| Energy class                           | <b>F</b>                 |
| Warranty                               | <b>2 years</b>           |

