

|                |                                                                                        |
|----------------|----------------------------------------------------------------------------------------|
| Product name   | <b>Asalite Premium LED Panel BackLit 120x30cm 36W 4000K (5400 lumens) LIFUD driver</b> |
| Product code   | <b>ASAL0262</b>                                                                        |
| EAN-code       | <b>5999565665418</b>                                                                   |
| Packaging unit | <b>1pcs, 6pcs/carton</b>                                                               |



## Technical Details

|                              |                           |
|------------------------------|---------------------------|
| Power                        | <b>36 W</b>               |
| Socket                       | <b>AC</b>                 |
| Luminosity                   | <b>5 400 lumen</b>        |
| Colour temperature           | <b>4 000 K</b>            |
| Driver                       | <b>LIFUD NON-FLICKER</b>  |
| Dimmable                     | <b>no</b>                 |
| IP protection                | <b>IP 20</b>              |
| Dimension                    | <b>1195 x 295 x 30 mm</b> |
| Power grid                   | <b>AC 220-240 V</b>       |
| Frequency                    | <b>50/60 Hz</b>           |
| Lifetime                     | <b>25 000 hours</b>       |
| On/Off Cycles                | <b>15 000</b>             |
| Shade colour                 | <b>opal</b>               |
| Technology                   | <b>SMD LED</b>            |
| Product form                 | <b>panel</b>              |
| Product material             | <b>metal/plastic</b>      |
| Product colour               | <b>white</b>              |
| Beam angle                   | <b>120 °</b>              |
| Luminous efficacy            | <b>150 lumen/watt</b>     |
| Colour rendering factor (Ra) | <b>&gt;80</b>             |
| Power factor (Pf)            | <b>&gt;0,9</b>            |
| UGR                          | <b>22</b>                 |
| Operating temperature        | <b>-20 °C- +40 °C</b>     |
| Product weight               | <b>1 900 g</b>            |
| Energy class                 | <b>D</b>                  |
| Warranty                     | <b>5 years</b>            |



Asalite Lighting Kft. certifies that our product is manufactured in accordance with European regulations and guidelines.



For indoor use.